

23 Rec'd PCT/PTO 23 OCT 1998

FORM PTO-1390 (REV 5-93)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY DOCKET NO. P3120-8014
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				DATE: October 23, 1998
				U.S. APPLN. NO. (IF KNOWN, SEE 37 CFR 1.5) 09/147175
INTERNATIONAL APPLICATION NO. PCT/FR97/00740		INTERNATIONAL FILING DATE April 24, 1997		PRIORITY DATE CLAIMED April 25, 1996
TITLE OF INVENTION: DEVICE FOR HOLDING A PAPER SHEET				
APPLICANT(S) FOR DO/EO/US: Etienne DILL and Joël SPAES				
1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. (THE BASIC FILING FEE IS ATTACHED)				
2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.				
3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT articles 22 and 39(1).				
4. <input checked="" type="checkbox"/> A proper demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.				
5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ul style="list-style-type: none"> a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US) 				
6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).				
7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ul style="list-style-type: none"> a. <input checked="" type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input type="checkbox"/> have not been made and will not be made. 				
8. <input checked="" type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).				
9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).				
10. <input checked="" type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).				
Items 11. to 16. below concern other document(s) or information included:				
11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.				
12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.				
13. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.				
14. <input type="checkbox"/> A substitute specification.				
15. <input type="checkbox"/> A change of power of attorney and/or address letter.				
16. <input checked="" type="checkbox"/> Other items or information: PCT/IPEA/408, Response to Written Opinion Check No. 17814 Drawings (5 sheets)				

U.S. APPLN. NO. (IF KNOWN, SEE 37 C.F.R. 1.50)

INTERNATIONAL APPLICATION NO. PCT/FR97/00740

ATTORNEY DOCKET NO. P3120-8014

DATE: October 23, 1998

17. ~~xx~~ The following fees are submitted:

Basic National Fee (37 CFR 1.492(a)(1)-(5):

Search Report has been prepared by the EPO or JPO.....\$930.00
International preliminary examination fee paid to USPTO (37 CFR 1.482).....\$720.00
No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)).....\$790.00
Neither international preliminary examination fee (37 CFR 1.482) or international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....\$1,070.00
International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4)\$ 98.00

CALCULATIONS

PTO USE ONLY

ENTER APPROPRIATE BASIC FEE AMOUNT =

\$930.00

Surcharge of \$130.00 for furnishing the oath or declaration later than _ 20 _ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

\$0

Claims

Number Filed

Number Extra

Rate

Total Claims

14 - 20 =

0

X \$ 22.00

\$0

Independent Claims

1 - 3 =

0

X \$ 82.00

\$0

Multiple dependent claim(s) (if applicable)

+ \$270.00

\$270.00

TOTAL OF ABOVE CALCULATIONS =

\$1,200.00

Reduction by 1/2 for filing by small entity, if applicable.
Verified Small Entity statement must also be filed.
(Note 37 CFR 1.9, 1.27, 1.28).

\$0

SUBTOTAL =

\$1,200.00

Processing fee of \$130.00 for furnishing the English translation later the _ 20 _ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).

\$0

TOTAL NATIONAL FEE =

\$1,200.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

\$0

TOTAL FEES ENCLOSED =

\$1,200.00

Amount to be refunded

\$

Charged


\$

- a. ☒ A check in the amount of \$1,200.00 to cover the above fees is enclosed.
b. ☐ Please charge my Deposit Account No. 14-1060 in the amount of \$_____ to cover the above fees. A duplicate copy of this sheet is enclosed.
c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 14-1060.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

NIKAIDO, MARMELESTEIN, MURRAY AND ORAM
Metropolitan Square
655 15th Street, N.W.
Suite 330 - G Street Lobby
Washington, D.C. 20005-5701
Telephone No. (202) 638-5000


George E. Oram, Jr.
Reg. No. 27,931

09/147175

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of:

Etienne DILL et al

Serial No.: New Application

Group Art Unit:

Filed: October 23, 1998

Examiner:

For: DEVICE FOR HOLDING A PAPER SHEET

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

October 23, 1998

Sir:

Prior to calculation of the filing fee and prior to the examination of this application,
please amend the above-identified application as follows:

IN THE CLAIMS:

Please amend the claims as follows:

Claim 4, line 1, change "any of the claims 1 to 3" to -- claim 1 --.

REMARKS

The above amendment to the claims has been made to correct the multiple dependency of the claim and to put the application into better condition for examination.

In the event that any fees are due in connection with this paper, please charge our
Deposit Account No. 14-1060.

Respectfully submitted,

NIKAIDO, MARMELESTEIN, MURRAY & ORAM LLP



George E. Oram, Jr.
Attorney for Applicants
Reg. No. 27,931

Atty. Docket No. P3120-8014

Metropolitan Square
655 15th Street, N. W.
Suite 330 - G Street Lobby
Washington, D. C. 20005-5701
Tel: (202) 638-5000

GEO:lad

PCT/FR97/00740

«Device for holding a paper sheet»

This invention relates to a device for holding a paper sheet close to the vertical in order to facilitate the viewing thereof.

5 Traditionally, copyholders of different types have been used to hold document vertically.

Some of these copyholders are made of a tilted tray on which the sheet is placed and held by a gripper located on the upper section of the tray. The tray, for its own part, is held by an articulated arm, by a trestle or
10 rests on a base. The tray-type copyholders are generally rather expensive. They are often cumbersome and fixed on the workspace (the desk) or a computer screen. Handling them can prove rather tedious.

Other copyholders are made of a gripper system clamping the document by its upper section, whereas the said document hangs freely in
15 the air. Such copyholders must be installed at a certain height on a fixed and vertical bracket. (They are generally fixed using a double-faced adhesive or a suction cup on a wall or the upper section of a computer screen). Their use depends on the presence of a fixed bracket which, however, is very tricky to displace and reading a text becomes difficult
20 since the mobile sheet may oscillate freely in the air.

The purpose of this invention is to remedy the shortcomings mentioned above.

More especially, the invention must suggest a solution enabling easier handling, let alone quicker handling, of the sheet to be held, during
25 placement.

The purpose of the invention is met by a device enabling to hold a paper sheet close to the vertical in order to facilitate the viewing thereof, which comprises first holding means and second holding means which cooperate with the first holding means in order to confer to the sheet, as
30 the former is introduced between the first and the second holding means, an initial curvature which rigidifies the sheet.

The device according to the invention is intended to be placed freely on a flat surface such as a worktop or at least more or less plane a surface, such as the top of a pile of books, papers or files. In this sense, the device of the invention can be a mobile device. Moreover, this device
 5 can be a small system designed to provide, thanks to an appropriate compromise between the surface that it occupies where placed at a given location and its weight as well as the tilt of the sheet when held, stable position and holding of the sheet.

The first holding means and the second holding means are formed
 10 so that the first holding means hold the sheet by its back and can thus be considered as back holding means and such that the second holding means hold the sheet by its front and can thus be considered as front holding means.

According to some embodiments presented further, the first holding
 15 means constitute the back section of the device whereas the second holding means constitute the front section of the device.

The device of the invention is more especially designed so that the sheet to be held can be introduced between the first holding means and the second holding means without prior deformation. The sheet is
 20 therefore still plane when being fed between the first holding means and the second holding means. As a user continues to feed the sheet between the first holding means and the second holding means, the device confers, by itself, an initial vertical folding or an initial curvature since the device does not deform the sheet to the extent that a folding mark may
 25 remain after the sheet has been removed from the device. The initial curvature created towards the upper angles of the sheet, two lines of force which stretch and rigidify the said sheet mechanically and permanently, for the duration of the insertion of the sheet between the first holding means and the second holding means, allowing the said sheet to be held
 30 in a position close to the vertical in a stable manner.

The device according to the invention advantageously grips the

sheet only by its lower edge and over a small height.

Although the device of the invention is mainly intended for holding one or several paper sheets, this device can also be used, without departing from the framework of this invention, for holding sheets made of
 5 any other material, such as for instance paper of different thicknesses, cardboard, synthetic material, liable to be deformed elastically for the duration of the holding process of this sheet by the device according to the invention. Moreover, the invention is not limited to the use of rectangular sheets exhibiting upper angles. But, conversely, sheets of any
 10 other shapes, for instance oval or circular, can be used.

The invention also relates to the characteristics thereunder, considered individually or according to all their technically possible combinations.

- The first holding means and the second holding means
 15 define amongst themselves a space designed for accommodating the sheet, whereas the aperture of this space shrinking in the direction of insertion of the sheet.

Seen in lateral projection, the first holding means or the back section of the device and the second holding means or the front section of the device, are at their upper level distant by a space of approx. 5 to 15
 20 mm so that the insertion of the sheet is made easier. This space shrinks towards the base of the space in order to exhibit at the base an aperture of approx. 0.2 to 3 mm. The aperture is measured, in lateral projection of the first holding means and the second holding means, as the width of the
 25 space between these means considered at the corresponding level. This shrinking can be more or less linear or, conversely, quite significant at the beginning and relatively small over the largest portion of the space.

- The first means exhibit a concave surface more or less tilted backwards and provided with two bearing zones and the second means
 30 exhibit a convex surface opposite the concave surface of the first holding means and fitted with a protrusion acting on the sheet in its section

arranged between both bearing zones.

- The concave surface comprises a recess provided by a contraction in the material of the first holding means.

- The first holding means are formed in order to exhibit mainly only bearing zones, whereas a portion of the first means located between the bearing zones is characterised at least partially by an absence of material.

This arrangement relates more particularly to two embodiments of the first holding means, i.e. a loop or a cradle on the one hand and sticks, spaced from one another, on the other.

- When the right and left hand sides of the back section are materialised by plane surfaces, the said surface can form together at the base of the device an open angle whose apex is directed to the back of the device and whose value may range from 90° to 160° , the value of 140° being particularly suited.

- When the bearing surfaces of the right and left hand sides of the back section are materialised by ridges, the protruding section can penetrate to such a depth that between these three points at the base of the device, an angle can be defined whose apex is represented by the protruding section and whose value may range from 90° to 160° , the value of 140° being particularly suited.

- The bearing surfaces of the back section can be tilted to form an angle of 45° to 85° , the value of 65° being particularly suited so that the plan of the sheet may form with the axis of the user's eye, a right angle.

- The first means and the second means or, according to a particular embodiment, the back and front sections, can be distant at the level of their upper opposite edges by a space of approx. 5 to 15 mm in order to facilitate the insertion of the sheet, whereas the value of 10 mm is particularly well suited.

- When the right and left hand bearing zones of the first means or of the back section are made of plane surfaces and when the said

surfaces are opposite plane surfaces constituting the second means or the front section, the distance between these sections may range from 0.2 to 3 mm, the value of 0.8 mm being particularly well suited.

- The back section can be mounted on an articulation
5 interconnected to an actuating device fitted with means to hold in position against the front section and which enable to move the back section away from the front section in order to facilitate the insertion of the sheet.

- The position holding means of the back section against the front
10 section can be a spring designed to recall automatically the back section against the front section and to bring the back section close to the front section by a gripping effect.

- The device according to the invention comprises, besides the first holding means and the second holding means, at least third holding means and fourth holding means. Whereas the first and second holding
15 means cooperate to hold a first sheet, the third and fourth holding means cooperate in order to confer to a second sheet, distant from the first one, an initial curvature which rigidifies this second sheet.

This arrangement enables to provide a device according to the invention comprising a number of holding means, whereas these means
20 are arranged in pairs, the first and second means forming a first pair, the third and fourth means forming a second pair and so on. This arrangement enables more particularly to hold a number of sheets placed behind one another and spaced from each other. Besides this aligned disposition, it is conceivable that the pairs of holding means are arranged
25 offset laterally or offset in decreasing height, for instance from the back to the front.

Other characteristics and advantages of the invention will be outlined by the description of a few embodiments illustrated thereunder with reference to the drawings. On these drawings:

30 Figure 1 represents, seen from a $\frac{3}{4}$ profile angle, a first embodiment of the device according to the invention.

Figure 2 represents the device of Figure 1, seen from the left.

Figure 3 represents the device of Figure 1 as a cross section along A-A.

Figure 4 represents an exploded view of the front and back sections of the device of Figure 1.

Figure 5 represents a cross section of a second embodiment of the device according to the invention.

Figure 6 represents, seen from a $\frac{3}{4}$ profile angle, a third embodiment of the device according to the invention.

Figure 7 represents the device of Figure 6 as a cross section along B-B.

Figure 8 represents, seen from a $\frac{3}{4}$ profile angle, the device of Figure 6 with a paper sheet.

Figure 9 represents, seen from a $\frac{3}{4}$ profile angle, a fourth embodiment of the device according to the invention.

Figure 10 represents the device of Figure 9 seen as a lateral projection.

Figure 11 represents, seen from a $\frac{3}{4}$ profile angle, an embodiment of a light device according to the invention.

Figure 12 represents the device of Figure 11 seen as a lateral projection.

Figure 13 represents, seen from a $\frac{3}{4}$ profile angle, an embodiment of the device according to the invention for several spaced sheets.

Figure 14 represents the device of Figure 13 seen as a lateral projection.

Figure 15 represents a variation of the device of Figure 6.

According to the embodiment represented on Figures 1 to 4, the device comprises a back section 1 and a front section 2 between which is defined a space 13 intended for accommodating a paper sheet 3 to be held. The rear section 1 is slightly tilted. Along its vertical axis of symmetry is also a recess 4 provided by a contracted zone in the material

of the back section and created for accommodating a protruding element 5 in the front section 2. Two bearing zones 8, 9 can be found on either side of the recess 4. When the user inserts the sheet 3 between both sections, back 1 and front 2 sections, the protruding element 5 of the front section which pushes the sheet 3 inside the recess 4 of the back section 1 forces the said sheet to form a fold or a curvature 6, which creates lines of force 7 spreading towards the upper corners of the sheet 3. The rigidity thus obtained is sufficient to hold the sheet 3 in immobile position.

In the embodiment according to Figures 1 to 4, the back section 1 exhibits a concave surface 14 tilted backwards and the front section exhibits a convex surface 15. The concave surface 14 comprises the bearing zones of the right 8 and left 9 hand sides of the back section 1 made of plane surfaces 16, 17 forming among them an open angle which corresponds to the folding degree of the sheet 3, whose apex is directed towards the back of the device and whose value ranges from 90° to 160°, whereas the value of 140° is particularly well suited to cause sufficient folding 6 at the bottom of the sheet 3 whereas this folding would not prove detrimental to the user when viewing the document.

The bearing zones 8, 9 are tilted backwards so that once the sheet has been inserted in the device, it lies approximately at right angle with respect to the user's eye in order to facilitate the viewing thereof. To take into account the mean height of the user in relation to the sheet, this tilt can have a value of 45° to 85°, whereas an angle of 65° is generally well suited.

The device of the invention such as represented on Figures 1 to 4 is composed of two separate sections 1 and 2 making up respectively the first and the second holding means of the device. The section 2 is fixed, for instance glued, on the section 1.

However, it is also conceivable that, as a variation, the device is single-block if made of a massive material or it can be formed, at least, of a shell open downwards and delineating the same space 13 as the device

according to Figures 1 to 4. In the latter case, the inside of the shell can be filled, at least partially, with a heavy material, possibly a granular material, such as metallic small shot, and enclosed by a plate.

The back section 1 and the front section 2 define between them a space 13 intended for accommodating the sheet 3 whose aperture a is much wider at the upper level of the device than at the base of the space 13. The space 13 whose aperture a_1 , measured at the upper level of the device corresponds to a value ranging from 5 mm to 15 mm, shrinks towards the bottom of the space, so that the space, seen along a cross section A-A from the front to the back of the device, exhibits the shape of a funnel enabling easy insertion of the sheet in the device. The surfaces 14 and 15 guide the sheet easily towards the bottom of the device where the recessed 4 and protruding 5 zones can be found.

On either side of the recess 4, the front 2 and back 1 sections exhibit opposite plane surfaces, separate at the base of the space 13 by a distance a_2 which may range from 0.2 mm to 3 mm, whereas the value of 0.8 mm is sufficient for easy insertion of one to five sheets of ordinary paper (80 g) whereby the folding conferred to the sheet is not marked permanently, even when the protruding section 5 is materialised by a ridge.

In the embodiment according to Figure 5, the back section is composed of a plate 31 and the front section of a plate 32 interconnected to a base plate 33. The plate 31 is articulated on an axis 10 situated at the base of the back section, parallel to the lower plane of the device and perpendicular to the bisectrix of the angle defined by the sides 8 and 9. The plate 31 is interconnected to a lever 11 which enables it to toggle away from the front section 32 when the user depresses the lever 11 in order to facilitate the insertion of the sheet 3. While the user depresses the lever 11, the plate 31 and the front section 32 form, temporarily, a space corresponding to the space 13 of the device according to Figures 1 to 4. A spring 12 tends to push the back section 1 against the front section

32 with sufficient pressure to force the sheet 3 to hug the shapes of the front and back sections.

In case when the device is made of a light material (plastic material), it is provided with removable attachment or counterweight means, such as a double-faced adhesive, under its base.

In the embodiment represented on Figures 6 to 8, the first holding means are constituted by an element 41, an arc of a circle or an oval arc, whose extremities are interconnected to a base plate 43. The extremities of the element 41 constitute bearing zones 48 and 40 whose function corresponds to the bearing zones 8 and 9 of the embodiment according to Figure 1. The second holding means are made of a tongue 42 shaped in order to exhibit a protruding section 45 performing the same function as the protrusion 5 of the embodiment according to Figure 1. The tongue 42 is linked by its lower end to the base plate 43.

Whereas each of the bearing zones 48 and 49 of the element 41 extends mainly in a given plane, the tongue 42 shows a curvature to obtain the protruding section 45. The inside of the element 41 encloses a zone 44 provided by the absence of material and fulfilling the same function as the recess 4 of the embodiment according to Figure 1. The element 41 thus formed and the tongue 42 thus formed constitute the funnel for the insertion of the sheet to be held as well as the bearing and protruding zones necessary for stable holding of the sheet 3. Figure 7 shows just this in a cross section along the B-B line specified in Figure 6. Figure 8 represents this layout with a sheet 3 inserted in the device according to the invention.

According to a variation represented on Figure 15, the element 41 and the tongue 42 can be linked to the base plate 43 by an articulation 46.

In the embodiment represented on Figures 9 and 10, the bearing surfaces of the back section are provided by ridges 51 and the protruding section, made of a ridge 52, penetrates between them at the level of the

base of a recess 54 to such a depth that between these three element, an open angle is delineated, whose apex is represented on the base of the protruding section 5 and whose value ranges from 90° to 160° , whereas the value of 140° is particularly well suited.

5 The ridges 51 and 52 are arranged and tilted in order to fulfil the functions the bearing surfaces 58, 59 corresponding to the bearing surfaces 8 and 9 of the embodiment according to Figure 1, as well as the functions of the protruding section 55 corresponding to the protrusion 5 of the said embodiment, while providing a space 53 in the shape of a funnel
10 in order to facilitate the insertion and the placement of the sheet to be held.

Besides the arrangement of the ridges 51 and 52, Figure 10 shows more particularly an advantage of the device according to the invention, common to all the embodiments. It relates to the small height h on which
15 the means representing the bearing zones of the first holding means and the protrusion of the second holding means overlap each other partially, seen as a lateral projection. The height h of this interaction zone is approx. 2 cm and is sufficient to confer, to the sheet to be held, sufficient curvature to ensure the requested rigidity of the sheet to be held.

20 The embodiment of the device according to the invention, such as represented on Figures 11 and 12 differs from the other embodiments described so far since it reminds of the shape of a sheet. This sheet, which is more or less rectangular, is curved, as seen as a lateral projection, and composed of a first section 61 and a second section 62,
25 separate by a space 63. The space 63 is delineated by an element 64 interconnected to the first section 61 and an element 65 interconnected to the second section 62, whereas the elements 64 and 65 are linked together at the base of the space 63. The elements 64 and 65 are folded or curved in order to constitute respectively bearing zones, a protrusion
30 and a space intended for accommodating the sheet to be held, whereas the space has the shape of a funnel shrinking downwards. The device in

general and the elements 64, 65 in particular, thus reproduce the essential sections and functions of the embodiment according to Figure 1.

The device of the invention according to the embodiment represented on Figures 11 and 12 can be made of synthetic material, such as for instance an ABS (acrylnitrile-butadiene-styrene) resin. The device of the invention is therefore easy to produce, for instance by injection. In order to obtain a stability comparable to that of a device manufactured according to the embodiment of Figure 1, the area of the support on which the device will rest, must be wide enough to guarantee that the centre of gravity of a sheet to be held for a range of selected sizes and weights, does not come out of the surface covered by the device.

Whereas the sizes of the device according to Figure 1 are approx. 4 cm in height, 6 cm in depth and 5 cm in width, with a weight of 110 to 120 g when it is filled with small shot, the sizes of the device according to Figure 11 become 5 cm in height and width, 12 cm in length. Its weight is approx. 25 g.

According to the embodiment represented on Figures 13 and 14, the device of the invention is formed by an oblong body comprising, in this order, a rear section 21, two intermediate sections 27, 28 and a front section 26, each of these sections being separate from the adjacent section by a space 13A, 13B or 13C intended for holding a sheet 3A, 3B or 3C. The spaces 13A, 13B and 13C are arranged at three different levels in order to place the sheets on staggered heights, which enables to receive them simultaneously.

Whereas the back section 21 and the front section 26 correspond, as regards their shapes and functions, respectively to the back section 1 and the front section 2 of the device according to Figure 1, the intermediate sections 27 and 28 are formed in order to fulfil the function of the front section as well as the function of the back section.

To this end, the intermediate section 27 is formed on the side 22

opposite the back section 21, as a front section and on the side 23 opposite the intermediate section 28, as a back section. In the same way, the intermediate section 28 comprises a side 24 arranged opposite the intermediate section 27 and shaped as a front section and a side 25 arranged opposite the front section and formed as a back section. Thus, the device comprises three pairs of holding means referred to respectively as 21/22, 23/24 and 25/26. The shapes and the functions of these means correspond essentially to those of the first and second holding means 1 and 2, their detailed description is omitted to avoid repetitions.

10 The holding device represented on Figures 13 and 14 is a single block, approx. 10 cm in length, 6 cm in width at the back and 5 cm at the front of the device, 6 cm at the back and 4 cm at the front of the device.

The device according to the invention is particularly intended for users who, within the framework of their activities, studies or leisure time, need to view easily a document on paper (text, drawing, picture, photo). It can be made of different materials such as for instance crystal, cast aluminium, bronze, stainless steel, sanded paper pulp, possibly coloured, and wood. In the light version, the device can be made of, besides ABS resins, any other plastic material, and particularly advantageously, polypropylene.

20 The space between the first and the second holding means can be obtained, notably for devices made of a non-cast massive material, by spark machining or any other appropriate abrasive process.

The reference signs inserted after the technical characteristics mentioned in the claims solely aim at facilitating the understanding of the latter and do not limit their extent in any way.

CLAIMS

1. A device enabling to hold a paper sheet close to the vertical in order to facilitate the viewing thereof, characterized in that it comprises first holding means (1) and second holding means (2) which cooperate
5 with the first holding means (1) in order to confer to the sheet (3) gradually, as the latter is introduced between the first and the second holding means (1, 2), an initial curvature which rigidifies the sheet (3).

2. A device according to claim 1, characterised in that the first holding means (1) and the second holding means (2) delineate among
10 them a space (13) intended for accommodating the sheet (3) and whose aperture (a) shrinks in the sense of introduction of the sheet.

3. A device according to claim 1 or 2, characterised in that the first means (1) exhibit a concave surface (14) slightly tilted backwards and provided with two bearing zones (8, 9) and the second means (2) exhibit a
15 convex surface (15) opposite the concave surface (14) and fitted with a protrusion (5) acting on the sheet in its section arranged between both bearing zones (8, 9).

4. A device according to claim 3, characterised in that the concave surface (14) comprises a recess (4) provided by a contraction in
20 the material of the first holding means (1)

5. A device according to claim 3, characterised in that the bearing zones (8, 9) of the first means (1) are composed of plane surfaces delineating between them at the base of the space (13) an obtuse angle whose apex is directed towards the back of the device and whose value
25 ranges from 90° to 160°.

6. A device according to claim 3, characterised in that the bearing zones (8, 9) of the first means (1) are materialised by ridges (16, 17) and in that the protruding section (5) penetrates to such a depth that between these three points at the base of the device (13), an angle can
30 be defined whose apex is represented by the protruding section (5) and whose value may range from 90° to 160°.

7. A device according to any of the claims 3 to 6, characterised in that the bearing zones (8, 9) of the first means (1) are tilted with respect to the horizontal plane in order to delineate an angle whose value ranges from 45° to 85°, so that the plane of the sheet (3) delineates with the axis of a user's eye, approximately a right angle.

8. A device according to claim 1 or 2, characterised in that the first means (41, 51) are formed in order to exhibit essentially bearing zones (8, 9) only, whereas a portion of the first means, between the bearing zones (8, 9) consists at least partially of an absence of material.

9. A device according to claim 1, characterised in that the first means (31) are mounted on an articulation (10) interconnected to an actuating body (11) fitted with holding means (12) in position against the second means (32), whereby the actuation of the said body (11) enables to spread the first means (31) from the second means (32) in order to facilitate the placement of the sheet (3).

10. A device according to claim 1, whose first and second holding means (21, 22) are intended for holding a first sheet (3A), characterised in that it comprises at least third holding means (23) and fourth holding means (24) working together with the third holding means (23) in order to confer at least to a second sheet (3B), spaced from the first sheet (3A), an initial curvature which rigidifies the second sheet (3B).

11. A device according to claim 1, characterised in that the first holding means are composed of a back section (1) fitted with at least two bearing zones, right and left (8, 9), slightly tilted backwards and between which is provided a recess (4), in that the second holding means (2) are composed of a front section (2) comprising opposite the recess (4) a protruding zone (5) intended for penetrating into the recess (4), whereas the sheet (3) to be held can be inserted between the back section (1) and the front section (2) so that during the introduction of the sheet (3) into the device, the protruding zone (5) confers at the bottom of the sheet (3) a vertical fold (6) curving the sheet and creating, towards the upper angles

of the sheet (3) lines of force (7) which stretch and rigidify the said sheet (3).

of the sheet (3) lines of force (7) which stretch and rigidify the said sheet (3).




FIG. 1




FIG. 2




FIG. 3




FIG. 4







FIG. 5






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

Declaration For U.S. Patent Application

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled (Insert Title) Device for holding a paper sheet

the specification of which

(Check one of blocks 1, 2, or 3. See note A on back of this page)

1. ☐ is attached hereto.2. ☒ was filed on April 24, 1997 as International PCT Application Serial No. PCT/FR 97/00740 and was amended on _____ (if applicable)3. ☐ was filed on _____ as U.S. Application Serial No. _____ and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application for which priority is claimed:

(Number)	(Country)	(Day/Month/Year Filed)	Priority Claimed <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
96 05218	FRANCE	25/04/1996	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
____	____	____	<input type="checkbox"/> Yes <input type="checkbox"/> No
____	____	____	<input type="checkbox"/> Yes <input type="checkbox"/> No
____	____	____	<input type="checkbox"/> Yes <input type="checkbox"/> No

List prior foreign applications. See note B on back of this page

See Note C on back of this page

☐ See attached list for additional prior foreign applications

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(List Prior U.S. Applications)

(Application Serial Number)

(Filing Date)

(Status) (patented, pending, abandoned)

(Application Serial Number)

(Filing Date)

(Status) (patented, pending, abandoned)

And I hereby appoint as principal attorneys David T. Nikaido, Reg. No. 22,663; Charles M. Marmelstein, Reg. No. 25,895; George E. Oram, Jr., Reg. No. 27,931; Robert B. Murray, Reg. No. 22,980; Martin S. Postman, Reg. No. 18,570; E. Marcie Emas, Reg. No. 32,131; Michael G. Gilman, Reg. No. 19,114; Douglas H. Goldhush, Reg. No. 33,125; Juan Carlos Marquez, Reg. No. 34,072; Robert L. Waddle, Reg. No. 35,795; Kevin C. Brown, Reg. No. 32,402; Monica F. Chin, Reg. No. 36,105.

Please direct all communications to the following address:

NIKAIDO, MARMELESTEIN, MURRAY & ORAM

Metropolitan Square

655 Fifteenth Street, N.W., Suite 330 - G Street Lobby

Washington, D.C. 20005-5701

(202) 638-5000 Fax: (202) 638-4810

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

(See Note D on back of this page) Full name of sole or first inventor

Etienne DILL

ETIENNE DILL

Inventor's signature

9th February 1999

Residence 28, rue Mehul - 93500 PANTIN - FRANCECitizenship FrenchPost Office Address Same as above

Full name of second joint inventor, if any

2-00
Joel SPAES

Joël SPAES

Inventor's signature

9th February 1999

Date

Residence 26, rue Gambetta - 92150 SURESNES - FRANCE

Citizenship French

Post Office Address Same as above

Full name of third joint inventor, if any

Inventor's signature

Date

Residence

Citizenship

Post Office Address

Full name of fourth joint inventor, if any

Inventor's signature

Date

Residence

Citizenship

Post Office Address

Full name of fifth joint inventor, if any

Inventor's signature

Date

Residence

Citizenship

Post Office Address

Full name of sixth joint inventor, if any

Inventor's signature

Date

Residence

Citizenship

Post Office Address

Full name of seventh joint inventor, if any

Inventor's signature

Date

Residence

Citizenship

Post Office Address

Full name of sixth joint inventor, if any

Inventor's signature

Date

Residence

Citizenship

Post Office Address